shown in Fig. 2,--;

Page 6, between lines 19 and 21, insert as a centered heading:
--DESCRIPTION OF THE PREFERRED EMBODIMENTS--.

IN THE CLAIMS

Please cancel claim 19, and amend the remaining claims as follows:

1. (amended) A changer apparatus for information discs, comprising:

a stacking unit for stacking at least two information discs in [at least two] respective stacking positions, a read/write unit for reading information stored on the information discs and/or writing information on the information discs in a play position,

- an eject position [being provided in] at which an information disc can be removed from the apparatus, and [characterized in that]

further comprising transport means [have been provided] for [the] transport of the information discs from the eject position into a loading position of the stacking unit along a curve-shaped loading path.

2. (amended) A changer apparatus as claimed in Claim 1,

[characterized in that] wherein the play position [has been provided] is between the eject position and the loading position.

40

3. (amended) A changer apparatus as claimed in Claim 1,

[characterized in that] wherein the play position is offset from

[the] a direct connecting line between the loading position and the eject position.

Sparket States

- 4. (amended) A changer apparatus as claimed in Claim 1,

 [characterized in that] wherein the play position is disposed on the loading path.
- 5. (amended) A changer apparatus as claimed in Claim 4,

 [characterized in that] further comprising a first transport

 mechanism [has been provided] for [the] transport of the

 information discs between the eject position, the play position and
 the loading position, and a second transport mechanism [has been

 provided] for [the] transport of the information discs into the

 stacking positions of the stacking unit, the first transport

 mechanism being adapted to move the information discs in the

 loading plane and the second transport mechanism being adapted to

 move the information discs in a stacking direction oriented

 vertically with respect to the loading plane.
- 6. (amended) A changer apparatus as claimed in Claim 5,

 [characterized in that] wherein the first transport mechanism

 comprises at least a first and a second guide for the disc edge of

the information disc, which guide is grooved and is movable in the loading plane, the second guide comprising at least one rotationally drivable first transport wheel.

S)

7. (amended) A/changer apparatus as claimed in Claim 6, [characterized in that] wherein:

the first guide is a passive supporting guide,

there [has been] is provided a third guide comprising a second transport wheel,

there [has been] <u>is</u> provided a passive supporting guide as a fourth guide,

the first, the second, the third and the fourth guide comprise pivotal arms which are supported at one end and which are pivotable in the loading plane,

the first the second, the third and the fourth guide are preloaded towards the curve-shaped loading path,

the first transport wheel is essentially adapted to move the information discs between the eject position and a transfer position and the second transport wheel is essentially adapted to move the information discs from the transfer position into the loading position.

8. (amended) A changer apparatus as claimed in Claim 7,

[characterized in that] wherein the first and the third guide are mounted on a common pivot.

- 9. (amended) A changer apparatus as claimed in Claim [1, characterized in that the] 7, wherein a read/write unit is movably supported on a chassis plate of the apparatus.
- 10. (amended) A changer apparatus as claimed in Claim [1, characterized in that] 9, wherein the read/write unit comprises a base plate and a laser mounting plate, the base plate and the laser mounting plate are coupled by means of dampers, the base plate is slidably mounted on the chassis plate, and the laser mounting plate carries a clamping device for clamping the information disc in the play position and an optical unit for reading information stored on the information disc.
- 11. (amended A changer apparatus as claimed in Claim [1, characterized in that] 9, wherein the read/write unit is movable into the play position in the vertical direction.
- 12. (amended) A changer apparatus as claimed in Claim [7, characterized in that] 9, wherein in the play position the first, [the] second, [the] third and [the] fourth [guide] guides are pivoted away from the disc edge of the information disc, and the pivoting away of the guides is controlled by [means of] the base plate of the read write unit or a sliding plate.
- 13. (amended) A changer apparatus as claimed in Claim 1,

 [characterized in that] wherein the stacking unit comprises at

least two holder compartments for holding one information disc each,

20

the holder compartments are coupled to at least one threaded spindle and [the holder compartments] are movable into a vertical direction by rotation of the spindles,

there [have been] is provided an upper stacking zone and a lower stacking zone [of] in the stacking unit for stacking the holder [compartment] compartments

the loading position [has been provided] is in a central zone between the upper and the lower stacking zone,

one of the holder compartments is each time movable into the loading position by rotation of the spindles, and the transport means are adapted to move the information disc from the holder compartment, which is in the loading position, into the play position and into the eject position.

- 14. (amended) A changer apparatus as claimed in Claim 13, [characterized in that] wherein in the axial direction of the spindles the central zone has spacing zones at both sides of the loading position, which spacing zones define an axial spacing between the holder compartment in its loading position and the axially adjacent holder compartments in their stacking positions.
- 15. (twice amended) A changer apparatus as claimed in Claim 13, [characterized in that] wherein the average screwthread pitch of the spindles in the loading position is smaller than the average